Top Coat for the 4EVER CONCRETE FLOOR

4EVER CONCRETE FLOOR WPF041

The clean color will be kept for a long time even in outdoor together with the enhanced durability

4EVER CONCRETE FLOOR WPF041 forms a coating with weatherproofing and durability which is suitable as the topcoat for 4EVER CONCRETE FLOOR.

Also prevents from degradation by UV and keeps its cosmetic advantage for a long time.







4EVER CONCRETE FLOOR WPF041

Suggested Mixture Ratio: Part A 4: Part B 1(weight)

Pot time (paint life) : 1 hour (at 20°C) 15 min. in Summer and 90 min. in Winter Hardening time for walk: Approx. 8 hours (at 20°C、60% humidity)

depends on the conditions such as room temperature, etc. : 10kg(PARTA/PARTB 5kg each)

Practical Coverage : 20 to 25 *Use as a topcoat for 4EVER CONCRETE FLOOR. : 20 to 25m

* Confirm that the floor paint(s) is hardened enough. * Paint Area is based on the single painting and varies on various conditions.

■ 4EVER CONCRETE FLOOR WPF041 Color sample

Name	Green	Light Green	Gray	Light Gray	Sky Blue	Orange	Yellow	Ivory	Brown	White
Japan Paint Manufacturers Association No	42-50L	39-60L	N-60	N-75	69-50T	12-50V	19-75X	22-80H	09-40L	N-95

Reducer for **4EVER CONCRETE FLOOR WPF041** Volume: 3.7L * Max reducer percentage is 5% against PARTA+PARTB weight.

*All items listed in the catalog are subject to change without prior notice

[Manufactures]

SOMAY-O TECHNOLOGY Inc.

5971-31, Morokurihashi, Goka-machi, Sashima-gun, Ibaraki 306-0313 Japan

TEL.0280-80-0005 FAX.0280-80-0006

E-mail:support@somayq.com http://www.somayq.com

[Main Agent]

CBC AMERICA LLC

2000 Regency Parkway, Suite 600 | Cary, NC 27518 www.cbcamerica.com **Chemicals & Pharmaceuticals Division** Jeff Crawford t: +1 919.230.2273